

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

policy

site/docs/modules/verae-access-authz/policy.md

verae-access-authz/policy

Package: verae-access-authz**Source:** packages/verae-access-authz/src/policy.js**Lines:** 101

What this module is

Implementation module in `verae-access-authz`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`POLICY`, `authorize`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>prefixAllowed</code>	<code>allow</code> , <code>subject</code>	—	<code>unknown</code>	see Call graph
<code>authorize</code>	<code>req</code>	—	<code>unknown</code>	see Call graph
<code>deny</code>	<code>plane</code> , <code>subject</code> , <code>reason</code>	—	<code>unknown</code>	see Call graph

What it imports / requires

- `./subjects.js`

Call graph (identifiers invoked)

`workers`, `freeze`, `web`, `prefixAllowed`, `some`, `endsWith`, `startsWith`, `authorize`,
`parseAddress`, `deny`, `includes`, `mismatch`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.