

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

# allow

site/docs/modules/verae-access-leaf/allow.md

## verae-access-leaf/allow

**Package:** verae-access-leaf**Source:** packages/verae-access-leaf/src/allow.js**Lines:** 29

## What this module is

---

Implementation module in `verae-access-leaf`. The tables below are extracted from the source (signatures + JSDoc).

## Exports

---

`leafAllowList`, `leafAllowed`

## Types / interfaces / classes

---

*None extracted.*

## Functions

---

| Name                       | Parameters           | Param types (JSDoc) | Returns              | Calls (same file / helpers) |
|----------------------------|----------------------|---------------------|----------------------|-----------------------------|
| <code>leafAllowList</code> | <code>(none)</code>  | —                   | <code>unknown</code> | see Call graph              |
| <code>leafAllowed</code>   | <code>subject</code> | —                   | <code>unknown</code> | see Call graph              |

## What it imports / requires

---

- `node:fs`

## Call graph (identifiers invoked)

---

`leafAllowList`, `existsSync`, `parse`, `readFileSync`, `leafAllowed`, `some`, `endsWith`, `startsWith`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

## Return values (how to read this)

---

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.