

zapier.georgelambert.org · Markdown indexes
VERAE TIME × ZAPIER

server

site/docs/modules/verae-access-web/server.md

verae-access-web/server

Package: verae-access-web

Source: packages/verae-access-web/src/server.js

Lines: 39

What this module is

Implementation module in `verae-access-web`. The tables below are extracted from the source (signatures + JSDoc).

Exports

No named `export` / `module.exports` keys detected.

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>json</code>	<code>code, obj</code>	—	<code>unknown</code>	see Call graph

What it imports / requires

- `node:http`
- `./gate.js`

Call graph (identifiers invoked)

`createServer`, `async`, `writeHead`, `end`, `stringify`, `json`, `match`, `statement`, `push`, `parse`,
`concat`, `toString`, `reload`, `listen`, `write`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.