

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

aggregate

site/docs/modules/verae-archive-aggregator/aggregate.md

verae-archive-aggregator/aggregate

Package: verae-archive-aggregator

Source: packages/verae-archive-aggregator/src/aggregate.js

Lines: 67

What this module is

Implementation module in `verae-archive-aggregator`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`aggregateAttached`, `mergeReceipts`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
aggregateAttached	<code>{ sha256, tenantId, kinds = ['publicMeta', 'privateMeta', 'file'], archives }</code>	<code>opts: object, opts.sha256: string, opts.tenantId: string, opts.kinds: string[], opts.timeoutMs: number</code>	<code>{ archivesQueried: boolean, archiveReplies: number, records: object[], silent: string[] — }</code>	see Call graph
mergeReceipts	<code>chainReceipts, archiveRecords</code>	<code>chainReceipts: object[], archiveRecords: object[]</code>	unknown	see Call graph

What it imports / requires

No imports detected.

Call graph (identifiers invoked)

`mock`, `aggregateAttached`, `query`, `push`, `includes`, `mergeReceipts`, `map`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.