

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

bloom

site/docs/modules/verae-archive-worm/bloom.md

verae-archive-worm/bloom

Package: verae-archive-worm**Source:** packages/verae-archive-worm/src/bloom.js**Lines:** 47

What this module is

Implementation module in `verae-archive-worm`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`Bloom`

Types / interfaces / classes

Kind	Name
class	<code>Bloom</code>

Functions

No top-level functions extracted.

Methods (class / object)

Name	Parameters
constructor	m = 16384, k = 4
hashes	s
add	s
mightHave	s

What it imports / requires

- `node:crypto`

Call graph (identifiers invoked)

`membership`, `constructor`, `alloc`, `ceil`, `hashes`, `createHash`, `update`, `digest`, `readUInt32BE`, `push`, `add`, `maybe`, `mightHave`, `every`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.