

zapier.georgelambert.org · Markdown indexes
VERAE TIME × ZAPIER

load

site/docs/modules/verae-fleet/load.md

verae-fleet/load

Package: verae-fleet

Source: packages/verae-fleet/src/load.js

Lines: 95

What this module is

Implementation module in `verae-fleet`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`FLEET_ROOT`, `readJson`, `loadFleet`, `listServices`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>readJson</code>	<code>file</code>	—	<code>unknown</code>	see Call graph
<code>loadFleet</code>	<code>root = FLEET_ROOT,</code> <code>opts = {}</code>	<code>root: string</code>	<code>unknown</code>	see Call graph
<code>listServices</code>	<code>loaded</code>	—	<code>unknown</code>	see Call graph

What it imports / requires

- `node:fs`
- `node:path`
- `node:url`
- `./machines.js`

Call graph (identifiers invoked)

`dirname`, `fileURLToPath`, `resolve`, `readJson`, `parse`, `readFileSync`, `loadFleet`, `join`,
`readdirSync`, `sort`, `endsWith`, `push`, `loadMachines`, `relative`, `listServices`, `values`, `map`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.