

zapier.georgelambert.org · Markdown indexes

VERAE TIME x ZAPIER

# **machines**

site/docs/modules/verae-fleet/machines.md

## **verae-fleet/machines**

**Package:** verae-fleet**Source:** packages/verae-fleet/src/machines.js**Lines:** 116

## **What this module is**

---

Implementation module in `verae-fleet`. The tables below are extracted from the source (signatures + JSDoc).

## **Exports**

---

`defaultMachines`, `loadMachines`, `normalizeMachine`, `upsertMachine`, `canHost`, `pickMachine`, `saveOverlay`

## **Types / interfaces / classes**

---

*None extracted.*

## Functions

| Name                          | Parameters                                                                                                                                                           | Param types (JSDoc)                                                                                              | Returns              | Calls (same file / helpers) |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|----------------------|-----------------------------|
| <code>defaultMachines</code>  | <code>(none)</code>                                                                                                                                                  | —                                                                                                                | <code>unknown</code> | see Call graph              |
| <code>loadMachines</code>     | <code>root,</code><br><code>overlayPath</code>                                                                                                                       | —                                                                                                                | <code>unknown</code> | see Call graph              |
| <code>normalizeMachine</code> | <code>m</code>                                                                                                                                                       | —                                                                                                                | <code>unknown</code> | see Call graph              |
| <code>upsertMachine</code>    | <code>list,</code> <code>spec</code>                                                                                                                                 | —                                                                                                                | <code>unknown</code> | see Call graph              |
| <code>canHost</code>          | <code>machine,</code><br><code>serviceId,</code><br><code>role</code>                                                                                                | —                                                                                                                | <code>unknown</code> | see Call graph              |
| <code>pickMachine</code>      | <code>machines,</code><br><code>instances,</code><br><code>serviceId,</code><br><code>role,</code> <code>exclude</code><br><code>= [],</code> <code>opts = {}</code> | <code>machines:</code><br><code>object[],</code><br><code>serviceId: string,</code><br><code>role: string</code> | <code>unknown</code> | see Call graph              |
| <code>saveOverlay</code>      | <code>overlayPath,</code><br><code>machines</code>                                                                                                                   | —                                                                                                                | <code>unknown</code> | see Call graph              |

## What it imports / requires

- `node:fs`
- `node:path`

## Call graph (identifiers invoked)

`defaultMachines`, `plane`, `loadMachines`, `join`, `existsSync`, `parse`, `readFileSync`, `isArray`, `upsertMachine`, `assign`, `map`, `normalizeMachine`, `trim`, `findIndex`, `push`, `canHost`, `includes`, `capacity`, `pickMachine`, `filter`, `has`, `sort`, `localeCompare`, `find`, `saveOverlay`, `mkdirSync`, `dirname`, `writeFileSync`, `stringify`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

## Return values (how to read this)

---

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.