

zapier.georgelambert.org · Markdown indexes
VERAE TIME × ZAPIER

server

site/docs/modules/verae-fleet/server.md

verae-fleet/server

Package: verae-fleet

Source: packages/verae-fleet/src/server.js

Lines: 146

What this module is

Implementation module in `verae-fleet`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`startControlServer`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>json</code>	<code>res, code, obj</code>	—	unknown	see Call graph
<code>startControlServer</code>	<code>sup, mon</code>	<code>sup: import('./supervisor.js').Supervisor, mon: import('./monitor.js').Monitor</code>	unknown	see Call graph

What it imports / requires

- `node:http`
- `node:fs`
- `node:path`
- `node:url`
- `./load.js`
- `../../verae-zapier-simulator/src/pipeline.js`

Call graph (identifiers invoked)

`bind, join, dirname, fileURLToPath, json, writeHead, end, stringify, import, startControlServer, createServer, async, snapshot, reset, push, parse, concat, toString, run, listServices, status, addMachine, match, checkMachine, setMachineEnabled, reconcile, startService, stopService, pauseService, resumeService, fn, pauseInstance, resumeInstance, restartInstance, stopInstance, markUnhealthy, createReadStream, pipe, startsWith, normalize, existsSync, statSync, isFile, extname, toLowerCase, listen, write`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).

- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.