

zapier.georgelambert.org · Markdown indexes

VERAE TIME x ZAPIER

ssh

site/docs/modules/verae-fleet/ssh.md

verae-fleet/ssh

Package: verae-fleet

Source: packages/verae-fleet/src/ssh.js

Lines: 171

What this module is

Implementation module in `verae-fleet`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`expandHome`, `shellQuote`, `sshTarget`, `sshBaseArgs`, `scpBaseArgs`, `sshExec`, `scpTo`,
`ensureRemoteRuntime`, `sshSpawnWorker`, `sshKillWorker`, `sshHttp`, `sshCheck`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>expandHome</code>	<code>p</code>	—	unknown	see Call graph
<code>shellQuote</code>	<code>s</code>	—	unknown	see Call graph
<code>sshTarget</code>	<code>machine</code>	—	unknown	see Call graph
<code>sshBaseArgs</code>	<code>machine</code>	—	unknown	see Call graph
<code>scpBaseArgs</code>	<code>machine</code>	—	unknown	see Call graph
<code>sshExec</code>	<code>machine,</code> <code>remoteCommand,</code> <code>{ timeoutMs = 8000 } = {}</code>	—	unknown	see Call graph
<code>scpTo</code>	<code>machine,</code> <code>localFiles,</code> <code>remoteDir</code>	—	unknown	see Call graph
<code>ensureRemoteRuntime</code>	<code>machine</code>	—	unknown	see Call graph
<code>sshSpawnWorker</code>	<code>machine,</code> <code>{ instance,</code> <code>env }</code>	—	unknown	see Call graph
<code>sshKillWorker</code>	<code>machine, pid,</code> <code>instance</code>	—	unknown	see Call graph
<code>sshHttp</code>	<code>machine,</code> <code>method,</code> <code>urlPath,</code> <code>{ port, body } = {}</code>	—	unknown	see Call graph
<code>sshCheck</code>	<code>machine</code>	—	unknown	see Call graph

What it imports / requires

- `node:child_process`

- `node:fs`
- `node:os`
- `node:path`
- `node:url`

Call graph (identifiers invoked)

`dirname`, `fileURLToPath`, `expandHome`, `homedir`, `startsWith`, `join`, `slice`, `shellQuote`, `replace`, `sshTarget`, `sshBaseArgs`, `existsSync`, `push`, `scpBaseArgs`, `sshExec`, `spawn`, `on`, `setTimeout`, `kill`, `reject`, `clearTimeout`, `concat`, `toString`, `trim`, `resolve`, `scpTo`, `ensureRemoteRuntime`, `has`, `add`, `sshSpawnWorker`, `entries`, `filter`, `map`, `split`, `pop`, `isFinite`, `sshKillWorker`, `sshHttp`, `stringify`, `parse`, `sshCheck`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.