

zapier.georgelambert.org · Markdown indexes  
VERAE TIME × ZAPIER

## server

site/docs/modules/verae-jobs-events/server.md

### verae-jobs-events/server

**Package:** verae-jobs-events

**Source:** packages/verae-jobs-events/src/server.js

**Lines:** 43

### What this module is

---

Implementation module in `verae-jobs-events`. The tables below are extracted from the source (signatures + JSDoc).

### Exports

---

No named `export` / `module.exports` keys detected.

### Types / interfaces / classes

---

None extracted.

### Functions

---

| Name                   | Parameters          | Param types (JSDoc) | Returns              | Calls (same file / helpers) |
|------------------------|---------------------|---------------------|----------------------|-----------------------------|
| <code>startNats</code> | <code>(none)</code> | —                   | <code>unknown</code> | see Call graph              |

### What it imports / requires

---

- `node:http`
- `./subjects.js`

## Call graph (identifiers invoked)

---

`startNats`, `import`, `connect`, `split`, `subscribe`, `parse`, `decode`, `respond`, `encode`, `stringify`, `createServer`, `writeHead`, `end`, `listen`, `write`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

## Return values (how to read this)

---

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.