

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

worker

site/docs/modules/verae-nats-process/worker.md

verae-nats-process/worker

Package: verae-nats-process**Source:** packages/verae-nats-process/src/worker.js**Lines:** 71

What this module is

Implementation module in `verae-nats-process`. The tables below are extracted from the source (signatures + JSDoc).

Exports

No named `export` / `module.exports` keys detected.

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>snapshot</code>	<code>(none)</code>	—	<code>unknown</code>	see Call graph
<code>json</code>	<code>code, obj</code>	—	<code>unknown</code>	see Call graph

Methods (class / object)

Name	Parameters
json	404, { error: 'not found' }

What it imports / requires

- node:http
- ./subjects.js
- ./handle.js

Call graph (identifiers invoked)

snapshot, createServer, async, writeHead, end, stringify, json, push, parse, concat, toString, handle, reply, listen, write, on, close, exit

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.