

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

identity

site/docs/modules/verae-zapier-middleware/lib/identity.md

verae-zapier-middleware/lib/identity

Package: verae-zapier-middleware**Source:** packages/verae-zapier-middleware/src/lib/identity.js**Lines:** 17

What this module is

Implementation module in `verae-zapier-middleware`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`normalizeVeraeUsername`, `stableVeraeUserId`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>normalizeVeraeUsername</code>	<code>username</code>	—	<code>unknown</code>	see Call graph
<code>stableVeraeUserId</code>	<code>username</code>	—	<code>unknown</code>	see Call graph

What it imports / requires

- `node:crypto`

Call graph (identifiers invoked)

`normalizeVeraeUsername`, `trim`, `toLowerCase`, `stableVeraeUserId`, `createHash`, `update`,
`digest`, `slice`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.