

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

# wait

site/docs/modules/verae-zapier-middleware/nats/wait.md

## verae-zapier-middleware/nats/wait

**Package:** verae-zapier-middleware**Source:** packages/verae-zapier-middleware/src/nats/wait.js**Lines:** 60

## What this module is

Implementation module in `verae-zapier-middleware`. The tables below are extracted from the source (signatures + JSDoc).

## Exports

`waitForJobEvent`

## Types / interfaces / classes

None extracted.

## Functions

| Name                         | Parameters                                    | Param types (JSDoc)                                                           | Returns                                                                      | Calls (same file / helpers) |
|------------------------------|-----------------------------------------------|-------------------------------------------------------------------------------|------------------------------------------------------------------------------|-----------------------------|
| <code>waitForJobEvent</code> | <code>jobId,</code><br><code>timeoutMs</code> | <code>jobId: string,</code><br><code>timeoutMs:</code><br><code>number</code> | <code>Promise&lt;object   null&gt;</code> — event payload or null on timeout | see Call graph              |
| <code>firstMatch</code>      | <code>async (</code>                          | —                                                                             | unknown                                                                      | see Call graph              |

## What it imports / requires

---

- `../debug/logger.js`
- `../debug/trace-context.js`
- `./subjects.js`
- `./connection.js`

## Call graph (identifiers invoked)

---

`createDebugger`, `waitForJobEvent`, `getNatsConnection`, `connectNats`, `subscribe`, `getTraceId`, `debug`, `setTimeout`, `resolve`, `async`, `parse`, `string`, `race`, `unsubscribe`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

## Return values (how to read this)

---

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.