

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

receiptRoutes

site/docs/modules/verae-zapier-middleware/routes/receiptRoutes.md

verae-zapier-middleware/routes/receiptRoutes

Package: verae-zapier-middleware**Source:** packages/verae-zapier-middleware/src/routes/receiptRoutes.js**Lines:** 46

What this module is

Implementation module in `verae-zapier-middleware`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`receiptRoutes`

Types / interfaces / classes

None extracted.

Functions

No top-level functions extracted.

Methods (class / object)

Name	Parameters
<code>asyncHandler</code>	<code>async (req, res)</code>

What it imports / requires

- `express`
- `../errors.js`
- `../services/timestampService.js`
- `../lib/receiptPdf.js`

Call graph (identifiers invoked)

`receipt`, `get`, `asyncHandler`, `async`, `toLowerCase`, `getJobStatus`, `toISOString`,
`buildReceiptPdf`, `setHeader`, `send`, `json`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.