

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

blobs

site/docs/modules/verae-zapier-middleware/store/blobs.md

verae-zapier-middleware/store/blobs

Package: verae-zapier-middleware

Source: packages/verae-zapier-middleware/src/store/blobs.js

Lines: 209

What this module is

Implementation module in `verae-zapier-middleware`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`decryptBlob`, `putBlob`, `getBlobRecord`, `readBlobPlaintext`, `createShare`, `redeemShare`, `putTree`, `getTree`, `createTreeShare`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
ensure	(none)	—	unknown	see Call graph
encrypt	plaintext, key	plaintext: Buffer, key: Buffer	unknown	see Call graph
decryptBlob	enc, key	key: Buffer	unknown	see Call graph
putBlob	{ tenantId, sha256, filename, bytes, publicMetadata = {}, privateMetadata = {} }	params: object, params.tenantId: string, params.sha256: string, params.filename: string, params.bytes: Buffer, params.publicMetadata: object, params.privateMetadata: object	unknown	see Call graph
getBlobRecord	id	—	unknown	see Call graph
readBlobPlaintext	id, tenantId	id: string, tenantId: string	unknown	see Call graph
createShare	{ blobId, fromTenantId, label }	—	unknown	see Call graph
redeemShare	token	token: string	unknown	see Call graph
putTree	{ tenantId, prefix, files }	—	unknown	see Call graph
getTree	id	—	unknown	see Call graph
createTreeShare	{ treeId, fromTenantId, label }	—	unknown	see Call graph

Methods (class / object)

Name	Parameters
<code>persist</code>	<code>(none)</code>
<code>persist</code>	<code>(none)</code>
<code>persist</code>	<code>(none)</code>
<code>persist</code>	<code>(none)</code>

What it imports / requires

- `node:crypto`
- `./db.js`

Call graph (identifiers invoked)

`ensure`, `getStore`, `encrypt`, `randomBytes`, `createCipheriv`, `concat`, `update`, `final`,
`getAuthTag`, `toString`, `decryptBlob`, `createDecipheriv`, `from`, `setAuthTag`, `putBlob`,
`randomUUID`, `toISOString`, `persist`, `getBlobRecord`, `readBlobPlaintext`, `createShare`,
`redeemShare`, `map`, `putTree`, `split`, `pop`, `push`, `getTree`, `createTreeShare`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.