

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

monitors

site/docs/modules/verae-zapier-simulator/monitors.md

verae-zapier-simulator/monitors

Package: verae-zapier-simulator**Source:** packages/verae-zapier-simulator/src/monitors.js**Lines:** 221

What this module is

Implementation module in `verae-zapier-simulator`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`analyze`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>analyze</code>	<code>events, ctx</code> <code>= {}</code>	<code>events: object[]</code> , <code>ctx: object</code>	<code>unknown</code>	see Call graph

What it imports / requires

No imports detected.

Call graph (identifiers invoked)

`check`, `filter`, `startsWith`, `includes`, `keys`, `join`, `broadcast`, `hop`, `analyze`, `push`, `map`, `find`, `some`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.