

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

server

site/docs/modules/verae-zapier-simulator/server.md

verae-zapier-simulator/server

Package: verae-zapier-simulator**Source:** packages/verae-zapier-simulator/src/server.js**Lines:** 88

What this module is

Implementation module in `verae-zapier-simulator`. The tables below are extracted from the source (signatures + JSDoc).

Exports

No named `export` / `module.exports` keys detected.

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>send</code>	<code>res, code, body, type = 'application/json; charset=utf-8'</code>	—	<code>unknown</code>	see Call graph
<code>readBody</code>	<code>req</code>	—	<code>unknown</code>	see Call graph

What it imports / requires

- `node:http`
- `node:fs`
- `node:path`
- `node:url`
- `./pipeline.js`

Call graph (identifiers invoked)

`dirname`, `fileURLToPath`, `join`, `send`, `stringify`, `writeHead`, `end`, `readBody`, `on`, `push`, `concat`, `toString`, `resolve`, `parse`, `reject`, `createServer`, `async`, `snapshot`, `reset`, `run`, `normalize`, `startsWith`, `existsSync`, `statSync`, `isDirectory`, `extname`, `createReadStream`, `pipe`, `listen`, `write`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.