

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

index

site/docs/modules/verae-zapier/index.md

verae-zapier/index

Package: verae-zapier**Source:** packages/verae-zapier/index.js**Lines:** 83

What this module is

Implementation module in `verae-zapier`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`version`, `platformVersion`, `authentication`, `beforeRequest`, `afterResponse`, `triggers`, `timestampCompleted`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>addApiKey</code>	<code>request</code> , <code>_z</code> , <code>bundle</code>	<code>request: object</code> , <code>_z: object</code> , <code>bundle: object</code>	<code>unknown</code>	see Call graph
<code>mapMiddlewareErrors</code>	<code>response</code> , <code>z</code>	<code>response: object</code> , <code>z: object</code>	<code>unknown</code>	see Call graph

What it imports / requires

- `./authentication`
- `./creates/timestamp_and_wait`
- `./creates/create_timestamp`
- `./creates/verify_timestamp`
- `./creates/batch_timestamp`
- `./creates/add_numbers`
- `./searches/job_status`
- `./searches/hash_lookup`
- `./searches/tree_lookup`
- `./triggers/timestamp_completed`
- `zapier-platform-core`
- `./package.json`

Call graph (identifiers invoked)

No local call identifiers extracted.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.