

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

persist

site/docs/modules/zapier-account-balance/persist.md

zapier-account-balance/persist

Package: zapier-account-balance**Source:** packages/zapier-account-balance/src/persist.js**Lines:** 29

What this module is

Implementation module in `zapier-account-balance`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`booksPath`, `loadInto`, `saveFrom`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>booksPath</code>	<code>(none)</code>	—	<code>unknown</code>	see Call graph
<code>loadInto</code>	<code>books</code>	—	<code>unknown</code>	see Call graph
<code>saveFrom</code>	<code>books</code>	—	<code>unknown</code>	see Call graph

Methods (class / object)

Name	Parameters
return	<code>process.env.BOOKS_PATH </code> <code>path.join(process.env.FLEET_STATE_DIR process.cwd(</code>

What it imports / requires

- `node:fs`
- `node:path`

Call graph (identifiers invoked)

`booksPath`, `join`, `cwd`, `loadInto`, `existsSync`, `load`, `parse`, `readFileSync`, `saveFrom`,
`mkdirSync`, `dirname`, `writeFileSync`, `stringify`, `dump`, `renameSync`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.