

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

## server

site/docs/modules/zapper-account-balance/server.md

## zapper-account-balance/server

**Package:** `zapper-account-balance`

**Source:** `packages/zapper-account-balance/src/server.js`

**Lines:** 101

### What this module is

---

Implementation module in `zapper-account-balance`. The tables below are extracted from the source (signatures + JSDoc).

### Exports

---

No named `export` / `module.exports` keys detected.

### Types / interfaces / classes

---

None extracted.

## Functions

| Name                   | Parameters                                    | Param types (JSDoc) | Returns              | Calls (same file / helpers) |
|------------------------|-----------------------------------------------|---------------------|----------------------|-----------------------------|
| <code>apply</code>     | <code>subject,</code><br><code>payload</code> | —                   | <code>unknown</code> | see Call graph              |
| <code>startNats</code> | <code>(none)</code>                           | —                   | <code>unknown</code> | see Call graph              |
| <code>readBody</code>  | <code>req</code>                              | —                   | <code>unknown</code> | see Call graph              |
| <code>reply</code>     | <code>sub, fn</code>                          | —                   | <code>unknown</code> | see Call graph              |
| <code>json</code>      | <code>code, obj</code>                        | —                   | <code>unknown</code> | see Call graph              |

## Methods (class / object)

| Name                  | Parameters                                                                    |
|-----------------------|-------------------------------------------------------------------------------|
| <code>saveFrom</code> | <code>books</code>                                                            |
| <code>reply</code>    | <code>nc.subscribe(SUBJECTS.STATEMENT_GET, { queue: SUBJECTS.QUEUE })</code>  |
| <code>reply</code>    | <code>nc.subscribe(SUBJECTS.BALANCE_GET, { queue: SUBJECTS.QUEUE })</code>    |
| <code>reply</code>    | <code>nc.subscribe(SUBJECTS.BALANCE_ADJUST, { queue: SUBJECTS.QUEUE })</code> |

## What it imports / requires

- `node:http`
- `./books.js`
- `./subjects.js`
- `./persist.js`

## Call graph (identifiers invoked)

---

`loadInto`, `apply`, `handle`, `saveFrom`, `startNats`, `import`, `connect`, `split`, `async`, `parse`,  
`decode`, `fn`, `respond`, `encode`, `stringify`, `reply`, `subscribe`, `write`, `readBody`, `on`, `push`,  
`resolve`, `concat`, `toString`, `createServer`, `writeHead`, `end`, `json`, `match`, `statement`, `listen`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

## Return values (how to read this)

---

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.