

zapier.georgelambert.org · Markdown indexes

VERAE TIME x ZAPIER

server

site/docs/modules/zapier-customer-service/server.md

zapier-customer-service/server

Package: zapier-customer-service**Source:** packages/zapier-customer-service/src/server.js**Lines:** 81

What this module is

Implementation module in `zapier-customer-service`. The tables below are extracted from the source (signatures + JSDoc).

Exports

No named `export` / `module.exports` keys detected.

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>statement</code>	<code>customerId</code>	—	<code>unknown</code>	see Call graph
<code>json</code>	<code>code, obj</code>	—	<code>unknown</code>	see Call graph

What it imports / requires

- `node:fs`

- `node:http`
- `node:path`
- `node:url`
- `./nats-billing.js`

Call graph (identifiers invoked)

`join`, `dirname`, `fileURLToPath`, `replace`, `statement`, `billingRequest`, `fetch`, `json`,
`createServer`, `async`, `writeHead`, `end`, `stringify`, `readFileSync`, `match`, `push`, `parse`,
`concat`, `toString`, `get`, `listen`, `write`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.