

zapier.georgelambert.org · Markdown indexes
VERAE TIME × ZAPIER

server

site/docs/modules/zapper-identity/server.md

zapper-identity/server

Package: `zapper-identity`

Source: `packages/zapper-identity/src/server.js`

Lines: 90

What this module is

Implementation module in `zapper-identity`. The tables below are extracted from the source (signatures + JSDoc).

Exports

No named `export` / `module.exports` keys detected.

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>handleBind</code>	<code>p</code>	—	unknown	see Call graph
<code>handleLookup</code>	<code>p</code>	—	unknown	see Call graph
<code>startNats</code>	<code>(none)</code>	—	unknown	see Call graph
<code>readBody</code>	<code>req</code>	—	unknown	see Call graph
<code>json</code>	<code>code, obj</code>	—	unknown	see Call graph

Methods (class / object)

Name	Parameters
<code>put</code>	<code>db, { customerId, ...bound }</code>

What it imports / requires

- `node:http`
- `./ids.js`
- `./store.js`
- `./subjects.js`

Call graph (identifiers invoked)

`load, handleBind, bindEmail, put, handleLookup, startNats, import, connect, split, async, subscribe, parse, decode, respond, encode, stringify, readBody, on, push, resolve, concat, toString, createServer, writeHead, end, json, match, listen, write`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).

- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.