

zapier.georgelambert.org · Markdown indexes
VERAE TIME × ZAPIER

store

site/docs/modules/zapper-identity/store.md

zapper-identity/store

Package: `zapper-identity`

Source: `packages/zapper-identity/src/store.js`

Lines: 31

What this module is

Implementation module in `zapper-identity`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`load`, `save`, `put`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
load	(none)	—	unknown	see Call graph
save	db	—	unknown	see Call graph
put	db, { customerId, veraeUserId, veraeUsername }	—	unknown	see Call graph
file	(none)	—	unknown	see Call graph

Methods (class / object)

Name	Parameters
save	db

What it imports / requires

- node:fs
- node:path

Call graph (identifiers invoked)

join, cwd, load, file, existsSync, parse, readFileSync, save, mkdirSync, dirname, writeFileSync, stringify, put

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).

- Pricing functions return integer **cents** on `Quote.totalCents`.