

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

ledger

site/docs/modules/zapier/ledger.md

zapier/ledger

Package: zapier**Source:** packages/zapier/src/ledger.ts**Lines:** 51

What this module is

Implementation module in `zapier`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`PrepaidRow`, `booksConfigured`, `ledgerAdjust`, `ledgerStatement`

Types / interfaces / classes

Kind	Name
type	<code>PrepaidRow</code>

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>booksUrl</code>	(none)	—	unknown	see Call graph
<code>booksConfigured</code>	(none)	—	unknown	see Call graph
<code>ledgerAdjust</code>	<code>row:</code> <code>PrepaidRow,</code> <code>plane:</code> <code>AccessPlane</code>	—	unknown	see Call graph
<code>ledgerStatement</code>	<code>customerId:</code> <code>string,</code> <code>plane:</code> <code>AccessPlane,</code> <code>veraeUserId?:</code> <code>string</code>	—	unknown	see Call graph

Methods (class / object)

Name	Parameters
<code>return</code>	<code>process.env.ACCOUNT_BALANCE_URL ''</code>
<code>return</code>	<code>await r.json(</code>

What it imports / requires

- `./billing-nats`

Call graph (identifiers invoked)

`booksUrl`, `replace`, `booksConfigured`, `ledgerAdjust`, `natsAdjust`, `fetch`, `stringify`, `json`, `ledgerStatement`, `natsStatement`, `encodeURIComponent`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.