

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

nats shim.d

site/docs/modules/zapier/nats-shim.d.md

zapier/nats-shim.d

Package: zapier**Source:** packages/zapier/src/nats-shim.d.ts**Lines:** 12

What this module is

Implementation module in `zapier`. The tables below are extracted from the source (signatures + JSDoc).

Exports

No named `export` / `module.exports` keys detected.

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>connect</code>	<code>opts:</code> <code>unknown</code>	—	<code>unknown</code>	see Call graph
<code>StringCodec</code>	(none)	—	<code>unknown</code>	see Call graph

What it imports / requires

No imports detected.

Call graph (identifiers invoked)

`connect`, `request`, `publish`, `close`, `encode`, `decode`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.