

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

verae bind

site/docs/modules/zapier/verae-bind.md

zapier/verae-bind

Package: zapier**Source:** packages/zapier/src/verae-bind.ts**Lines:** 90

What this module is

Implementation module in `zapier`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`normalizeVeraeUsername`, `stableVeraeUserId`, `VeraeBind`, `bindVeraeUser`

Types / interfaces / classes

Kind	Name
type	<code>VeraeBind</code>

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>normalizeVeraeUsername</code>	<code>username:</code> <code>string</code>	—	<code>unknown</code>	see Call graph
<code>stableVeraeUserId</code>	<code>username:</code> <code>string</code>	—	<code>unknown</code>	see Call graph
<code>mockBind</code>	<code>email:</code> <code>string</code>	—	<code>unknown</code>	see Call graph
<code>bindVeraeUser</code>	<code>email:</code> <code>string</code> , <code>customerId?:</code> <code>string</code>	—	<code>unknown</code>	see Call graph
<code>login</code>	<code>username:</code> <code>string</code> , <code>pass:</code> <code>string</code>	—	<code>unknown</code>	see Call graph

What it imports / requires

- `crypto`

Call graph (identifiers invoked)

`normalizeVeraeUsername`, `trim`, `toLowerCase`, `stableVeraeUserId`, `createHash`, `update`,
`digest`, `slice`, `mockBind`, `bindVeraeUser`, `replace`, `fetch`, `stringify`, `json`, `randomBytes`,
`toString`, `async`, `login`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).

- Pricing functions return integer **cents** on `Quote.totalCents`.